



DYREF G 50

SCALING INHIBITOR FOR COOLING SYSTEMS AND SUBSIDIARIES

PURPOSES



We recommend using our mixture on semi-open circuits supplied by corrosive raw water.

In these conditions, it represents the ideal choice thanks to the combination of antiscaling, anticorrosion and dispersant effects which gives it its active principles.

Solution based on plant actives, both anti-scale and dispersing, because :

- 1- Increases the solubility limit of salts and that of fur.
- 2- Changes the nature of the crystalline system as soon as the germination of the first crystals begins preventing their proliferation and scaling is therefore avoided.
- 3- Prevents the deposition of suspended matter.

It doesn't form deposit in the event of overdosing.

BENEFITS

Solution ready to use without prior dilution, injected proportionally to the make-up (subservient to an impulse meter).

Improves heat exchange by preventing the formation of tartar.

Complies with effluent standards in the correct dose.

Does not increase water salinity : Water saving at the blowdown.

INJECTION

It will be done through a dosing station proportionate to the make-up water which makes it possible to considerably reduce the time devoted to the implementation of the water treatment of the semi-open cooling circuits.

The dose rate will be adjusted by our technical service according to :

- the admissible concentration rate N in the Tower system,
- the installation in operation,
- the manufacturer's instructions,
- the quality of the make-up water (RYZNAR index, saturation rate, etc.).

In order to ensure proper implementation, you can use an analysis kit provided by us. Contact us for further information.

In order to ensure proper operation of a "cooling tower" installation, regular analysis of the physicochemical parameters (pH, TH, TA, TAC, CI and Cond.) should be carried out on the feed water and the network water.

However, a regular reading of the make-up water meters and follow-up of the network's water conductivity will enable the technician to easily track proper running of the installation. Contact us.

HANDLING & STORAGE

It is recommended to take customary precautions while handling chemicals (gloves, glasses ...). Consult the Safety Data Sheet (SDS).

The products must be kept away from frost.

CHARACTERISTICS

Physical	Liquid
Color :	Brown
Odor :	Aromatic
pH :	6,0

PACKAGING

it is available in 20, 210 and 800 kg, non returnable plastic drums.

For any other packaging please contact us.



Note : Do not mix the undiluted product with other chemical compounds without consulting us first.

The information and recommendations contained in this instruction manual are based upon our joint work with our customers and our current knowledge. They are provided merely as an indication and do not constitute an obligation of result. Date : 22/04/2024.

